

2022 ROUGHRIDER DAYS
CHAIN RULES

RULES FOR CLASS:

ALL CARS MUST REMAIN STOCK UNLESS SPECIFIED BELOW! THIS IS A CHAIN CLASS. THE ONLY WELDING ALLOWED IS FOR THE CAGE AND DRIVER'S DOOR STRAPS ONLY. IF MAGIC HELPER ELVES SOMEHOW SHOW UP AT YOUR SHOP AND WELD ENDS UP IN ANY OTHER PLACE OTHER THAN THOSE TWO PLACES YOU HAVE 3 OPTIONS. 1) BRING A TORCH TO SLICE MAGIC WELD SO TECHS CAN SEE DAYLIGHT THROUGH IT. 2) RUN THE MAIN CLASS WITH THE WELD CARS. 3) LEAVE YOUR CAR ON THE TRAILER.

THE REST OF THESE RULES ARE WHAT YOU CAN DO TO PREPARE YOUR CAR FOR THIS SHOW. THIS STUFF IS MAINLY FOR THE SAFETY OF YOURSELF AND THE OTHER DRIVERS.

1. This is a chain show. Mainly for beginners but also for the group of drivers that want to hang out with their friends and family in the shop for a few nights and put together something to run at this show. Don't bring an Imperial, Suicide Lincoln, or 03+ FOMOCO product.
2. ALL chrome, door handles, glass, body molding etc. must be removed. ALL interior must be removed. Removal of the dashboard and driver's door panel are optional. Original gas tank must be removed from car.
3. Fuel tanks must be mounted securely inside the car, behind the driver's seat. 10 gallon max capacity. Must be an approved fuel tank (boat tanks are ok). MUST BE A METAL TANK! NO PLASTIC FUEL TANKS.
4. You may have a minimum of 1 maximum of 2 bars mounted from the firewall to the roof in the windshield area (maximum of 3 inch material #9 wire or chain). If running bars you may only use 2 3/8"x5" max bolts per end of bar.
5. ABSOLUTELY NO WELDING!!!!
6. Trimming corners of bumpers and fender wells is ok.
7. Hoods must be chained, wired, or bolted shut (maximum of 3/8" chains, 3 loops of #9 wire, 1/2" bolts). NO WELDING SHUT. Maximum of 4 points. Single wrap chain only. Hinges DO NOT count as points.
8. Trunks must be chained, wired, or bolted shut. NO WELDING. Maximum of 6 points. Single wrap chain, 3 loops of #9 wire, or 1/2" x 6" bolts. Hinges DO NOT count as points.
9. Doors must be chained, wired, or bolted shut. NO WELDING OTHER THAN DRIVER'S DOOR. Maximum of 4 points. Single wrap chain or #9 wire or 1/2" bolts.
10. No frame chains.
11. Body bolts and mounts must remain stock and in stock location. No adding extra body bolts
12. No suspension modifications allowed. Overload springs must be removed. Aftermarket shackles must be removed or lowered to lowest point. Steering and shocks may not be modified. No aftermarket steering knuckles or columns.
13. Motors and transmissions must remain completely stock and in stock location. You may change families of powertrain. Motors and transmissions must be mounted with factory stock mounts and may be fastened securely with chain only (1 per side). No engine cradles (NO WELDING OF ANY FORM).
14. Radiators must remain stock and in stock location. Fans may be removed. No wire mesh between radiator and fan. NO OTHER COOLING IS ALLOWED! Aluminum radiators are ok.
15. Transmission coolers may be used if they are mounted securely in the rear seat area. Cooler lines must be steel or hydraulic hose.
16. Carburetor linkage and transmission linkage may be modified. Carburetor may have a wire or cable running from throttle on carburetor to the inside of the car as a backup. Aftermarket throttle and brake pedal assemblies are allowed.
17. Exhaust must be cut a minimum of 3 feet from the manifold. Headers through the hood are allowed.
18. Batteries must be moved inside of the car to the front passenger floor area, mounted securely, and covered.
19. All cars must have working brakes.
20. No frame modifications or reinforcement.
21. Pre-bending body tin and frame notching is ok. NO REWELDING NOTCHES IN FRAME. No cold-tilting.

22. Maximum of 16" wheel. No split rims. Any air filled tire is allowed. Tire flaps also allowed. You may also have a 8" weld in center.
23. 2 holes must be cut in hood one on each side of carburetor to aid in extinguishing fires.
24. Shock bumpers may be fastened securely with CHAIN OR WIRE ONLY (1 loop chain, or 3 wraps #9 wire) in a fashion as to prevent them from falling off. Shock bumpers must be mounted with factory stock mounts and bolts only. Bumper height must not exceed 18" to bottom of bumper. Stock bumpers only. Bumper swapping is fine be it must be a factory bumper off of a passenger car.
25. Rear ends must be of passenger car origin. Locked, posi, or spool is ok. No truck rear ends. Must have stock factory style driveshaft. No aftermarket sliders. REARENDS MUST BE BOLTED IN. NO BRACED HOUSING.
26. For drivers safety a cage is mandatory. A floating cage can be made out of 6 inch material welded to sheet metal ONLY. Side bars may be 12" material but must be a minimum of 4 inches off the floor. You are allowed a halo bar. The gas tank mount maybe attached to seat bar and must be minimum 4 inches from ALL sheet metal. You may run bars off of halo to the gas tank mount to allow more securement No down bars allowed.

Cory Miller-701-495-8235